



AFP7PSA2 | FP7 Power supply units



Product Number	AFP7PSA2
Part Number	AFP7PSA2
Product	FP7 Power supply units
Product name	FP7 Power supply units

※Photo may vary from actual product.



Spec Detail

As of May 29, 2023

Specifications and design of the products are subject to change without notice for the product improvement.

Item	Specifications
Product Number	AFP7PSA2
Part Number	AFP7PSA2
[[SPECIFICATIONS]]Rated input voltage	100-240 V AC
[[SPECIFICATIONS]]Allowable input voltage range	85-264 V AC
[[SPECIFICATIONS]]Input power supply frequency	47 to 63 Hz
[[SPECIFICATIONS]]Inrush current	40 A or less (Note) On cold starting
[[SPECIFICATIONS]]Input current	1.25 A or less
[[SPECIFICATIONS]]Rated output current (at 24 V)	1.8 A
[[SPECIFICATIONS]]Alarm contact capacity	1 A (30 V DC)
[[SPECIFICATIONS]]Remaining lifespan counting function	Available (Note) Notify by CPU unit
[[COMMON GENERAL SPECIFICATIONS]]Ambient temperature	0 to +55 °C +32 to +131 °F, Storage: -40 to +70 °C -40 to +158 °F
[[COMMON GENERAL SPECIFICATIONS]]Ambient humidity	10 to 95 % RH (at +25 °C +77 °F, no condensation), Storage: 10 to 95 % RH (at +25 °C +77 °F, no condensation)
[[COMMON GENERAL SPECIFICATIONS]]Vibration resistance	5 to 8.4 Hz, single amplitude of 3.5 mm 0.138 in, 1 sweep/min. (IEC 61131-2); 8.4 to 150 Hz, constant acceleration of 9.8 m/s ² , 1 sweep/min. (IEC 61131-2), 10 times each in X, Y, and Z directions
[[COMMON GENERAL SPECIFICATIONS]]Shock resistance	147 m/s ² or more , 3 times each in X, Y, and Z directions (IEC61131-2)
[[COMMON GENERAL SPECIFICATIONS]]Noise immunity	1,000 V [p-p] with pulse width 50 ns and 1 micro s (using a noise simulator)
[[COMMON GENERAL SPECIFICATIONS]]Operating condition	Free from corrosive gasses and excessive dust
[[INDIVIDUAL GENERAL SPECIFICATIONS]]Rated voltage range	100 to 240 V AC
[[INDIVIDUAL GENERAL SPECIFICATIONS]]Current consumption	1,250 mA or less

[[INDIVIDUAL GENERAL SPECIFICATIONS]]Net weight	290 g approx.
---	---------------

© Panasonic Industry Co., Ltd.